

Version January 2020





MRSL Instructions:

Chapter 1: VAUDE MRSL for Textiles and Coated Fabric Processing

This section applies to chemical formulations and substances used during the creation and wet processing of textile fibres, and during the creation of coated fabrics

Chapter 2: VAUDE MRSL for Natural Leather Processing

This section applies to chemical formulations and substances used throughout the production of natural leather, from rawhide to finished leather.

MRSL Groups:

GROUP A: Raw Material and Finished Product Supplier Guidance

Group A substances are banned from intentional use in facilities that process raw materials and manufacture finished products like fabrics. Please see VAUDE RSL for individual requirements on other substances



Group B: Chemical Supplier Formulation Limit

Group B substances are restricted to concentration limits in chemical formulations commercially available from chemical suppliers. These limits ban intentional use while allowing reasonable expected manufacturing impurities that should consistently achievable by responsible chemical manufacturers



CHAPTER 1: MRSL for Textiles and Synthetic Leather Processing

CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Apparel and Footwear Textile Processing	General Techniques for Analysing Chemicals
Alkylphenol (AP) and	d Alkylphenol Ethoxylates (APEOs): including all is	omers			
104-40-5					
11066-49-2	Nonylphenol (NP), mixed isomers		250 ppm		
25154-52-3	Honyiphenor (Hr.), mixed isomers		230 рріп		
84852-15-3				APEOs can be used as or found in:	
140-66-9				THE CONTROL OF THE CO	
1806-26-4	Octylphenol (OP), mixed isomers		250 ppm	detergents, scouring agents, spinning oils, wetting agents, softeners, emulsifier/dispersing agents for dyes	Liquid chromatography- mass spectrometry (LC-
27193-28-8		L			
9002-93-1		No intentional use	500 ppm	and prints, impregnating agents, de-	MS), gas chromatography-
9036-19-5	Octylphenol ethoxylates (OPEO)			gumming for silk production, dyes and pigment preparations, polyester padding and down/feather fillings.	mass spectrometry (GC-
68987-90-6					MS)
9016-45-9					
26027-38-3					
37205-87-1	Nonylphenol ethoxylates (NPEO)		500 ppm		
68412-54-4					
127087-87-0					
Chlorobenzenes and	Chlorotoluenes				
95-50-1	1,2-dichlorobenzene		1000 ppm	Chlorobenzenes and chlorotoluenes	
Other isomers of mo	Other isomers of mono-, di-, tri-, tetra-, penta- and hexa- hlorobenzene and mono-, di-, tri-, tetra- and penta- chlorotoluene			(chlorinated aromatic hydrocarbons)	
				can be used as carriers in the dyeing	GC-MS
			Sum = 200 ppm	process of polyester or wool/polyester	GC-IVIS
				fibres. They can also be used as	
				solvents.	



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Apparel and Footwear Textile Processing	General Techniques for Analysing Chemicals
Chlorophenols					
25167-83-3	Tetrachlorophenol (TeCP)		Sum = 20 ppm		
87-86-5	Pentachlorophenol (PCP)		Sum = 20 ppm		
4901-51-3	2,3,4,5-tetrachlorophenol				
58-90-2	2,3,4,6-tetrachlorophenol				
935-95-5	2,3,5,6-tetrachlorophenol				
95-57-8	2-chlorophenol			Chlorophenols are polychlorinated compounds used as preservatives or pesticides. Pentachlorophenol (PCP) and tetrachlorophenol (TeCP) have been used in the past to prevent mould	
120-83-2	2,4-dichlorophenol				
583-78-8	2,5-dichlorophenol				
87-65-0	2,6-dichlorophenol				GC-MS
95-95-4	2,4,5-trichlorophenol	No intentional use			
88-06-2	2,4,6-trichlorophenol		Sum = 50 ppm		EN ISO 17070
591-35-5	3,5-dichlorophenol				
576-24-9	2,3-dichlorophenol			when storing/ transporting, raw hides and leather. They are now regulated	
95-77-2	3,4-dichlorophenol			and leather. They are now regulated and should not be used.	
108-43-0	3-chlorophenol			and should not be used.	
106-48-9	4-chlorophenol				
15950-66-0	2,3,4-trichlorophenol				
933-78-8	2,3,5-trichlorophenol				
609-19-8	3,4,5-trichlorophenol				



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Apparel and Footwear Textile Processing	General Techniques for Analysing Chemicals
Dyes - Azo (Forming	Restricted Amines)				
101-14-4	4,4'-methylene-bis-(2-chloro-aniline)		150 ppm		
101-77-9	4,4'-methylenedianiline		150 ppm		
101-80-4	4,4'-oxydianiline		150 ppm		
106-47-8	4-chloroaniline		150 ppm		
119-90-4	3,3'-dimethoxylbenzidine		150 ppm		
119-93-7	3,3'-dimethylbenzidine		150 ppm		LC, GC
120-71-8	6-methoxy-m-toluidine		150 ppm		
137-17-7	2,4,5-trimethylaniline		150 ppm]	
139-65-1	4,4'-thiodianiline]	150 ppm	Azo dyes and pigments are colourants that incorporate one or several azo groups (-N=N-) bound with aromatic compounds. Thousands of azo dyes exist, but only those that degrade to form the listed cleavable amines are restricted. Azo dyes that release these amines are regulated and should no longer be used for dyeing of textiles.	
60-09-3	4-aminoazobenzene		150 ppm		
615-05-4	4-methoxy-m-phenylenediamine		150 ppm		
838-88-0	4,4'-methylenedi-o-toluidine	No intentional use	150 ppm		
87-62-7	2,6-xylidine	No intentional use	150 ppm		
90-04-0	o-anisidine		150 ppm		
91-59-8	2-naphthylamine]	150 ppm		
91-94-1	3,'3-dichlorobenzidine]	150 ppm		
92-67-1	4-aminodiphenyl		150 ppm	longer be used for dyeing or textiles.	
92-87-5	Benzidine]	150 ppm	1	
95-53-4	o-toluidine]	150 ppm	1	
95-68-1	2,4-xylidine]	150 ppm	1	
95-69-2	4-chloro-o-toluidine]	150 ppm	1	
95-80-7	4-methyl-m-phenylenediamine]	150 ppm	1	
97-56-3	o-aminoazotoluene]	150 ppm	1	
99-55-8	5-nitro-o-toluidine]	150 ppm		
Dyes - Navy Blue Co	lourant				
118685-33-9	Component 1: C39H23ClCrN7O12S-2Na			Navy Blue colourants are regulated and	
Not Allocated	Component 2: C46H30CrN10O20S2·3Na	No intentional use	250 ppm	should no longer be used for dyeing of textiles.	LC



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Apparel and Footwear Textile Processing	General Techniques for Analysing Chemicals
Dyes – Carcinogeni	c or Equivalent Concern				
1937-37-7	C.I. Direct Black 38		250 ppm		
2602-46-2	C.I. Direct Blue 6		250 ppm		
3761-53-3	C.I. Acid Red 26		250 ppm		
569-61-9	C.I. Basic Red 9		250 ppm]	
573-58-0	C.I. Direct Red 28		250 ppm		
632-99-5	C.I. Basic Violet 14		250 ppm	Most of these substances are regulated	
2475-45-8	C.I. Disperse Blue 1	No intentional use	250 ppm	and should no longer be used for dyeing	LC
2475-46-9	C.I. Disperse Blue 3		250 ppm	of textiles.	
2580-56-5	C.I. Basic Blue 26 (with Michler's Ketone > 0.1%)		250 ppm		
569-64-2	C.I. Basic Green 4 (malachite green chloride)		250 ppm		
2437-29-8	C.I. Basic Green 4 (malachite green oxalate)		250 ppm		
10309-95-2	C.I. Basic Green 4 (malachite green)		250 ppm		
82-28-0	Disperse Orange 11		250 ppm		
Dyes – Disperse (Se	ensitising)				
119-15-3	Disperse Yellow 1		250 ppm		
12222-97-8	Disperse Blue 102		250 ppm		
12223-01-7	Disperse Blue 106		250 ppm	1	
12236-29-2	Disperse Yellow 39		250 ppm		
13301-61-6	Disperse Orange 37/59/76		250 ppm		
23355-64-8	Disperse Brown 1		250 ppm	Disperse dyes are a class of water-	
2581-69-3	Disperse Orange 1		250 ppm	insoluble dyes that penetrate the fibre	
2832-40-8	Disperse Yellow 3		250 ppm	system of synthetic or manufactured	
2872-48-2	Disperse Red 11		250 ppm	fibres and are held in place by physical	
2872-52-8	Disperse Red 1	No intentional use	250 ppm	forces without forming chemical bonds.	LC
3179-89-3	Disperse Red 17		250 ppm	Disperse dyes are used in synthetic fibre	
3179-90-6	Disperse Blue 7		250 ppm	(e.g., polyester, acetate, polyamide). Restricted disperse dyes are suspected	
3860-63-7	Disperse Blue 26		250 ppm	of causing allergic reactions and should	
54824-37-2	Disperse Yellow 49		250 ppm	no longer be used for dyeing of textiles.	
12222-75-2	Disperse Blue 35		250 ppm	no longer be used for dyenig of textiles.	
61951-51-7	Disperse Blue 124		250 ppm]	
6373-73-5	Disperse Yellow 9		250 ppm]	
730-40-5	Disperse Orange 3		250 ppm	1	
56524-77-7	Disperse Blue 35		250 ppm	1	



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Apparel and Footwear Textile Processing	General Techniques for Analysing Chemicals
Flame Retardants					
115-96-8	Tris(2-chloroethyl)phosphate (TCEP)		250 ppm		
1163-19-5	Decabromodiphenyl ether (DecaBDE)		250 ppm		
126-72-7	Tris(2,3,-dibromopropyl)-phosphate (TRIS)		250 ppm		
32534-81-9	Pentabromodiphenyl ether (PentaBDE)		250 ppm		
32536-52-0	Octabromodiphenyl ether (OctaBDE)		250 ppm	glassa sakasadasak ah asalas la asas sasah.	
5412-25-9	Bis(2,3-dibromopropyl)phosphate (BIS)		250 ppm	Flame retardant chemicals are rarely	
545-55-1	Tris(1-aziridinyl)phosphine oxide) (TEPA)	No intentional use	250 ppm	used to meet flammability requirements in children's clothing and	GC-MS
59536-65-1	Polybromobiphenyls (PBB)	No intentional use	250 ppm	adult products. They should no longer	GC-WIS
79-94-7	Tetrabromobisphenol A (TBBPA)		250 ppm	be used in apparel and footwear.	
3194-55-6	Hexabromocyclodecane (HBCDD)		250 ppm		
3296-90-0	2,2-bis(bromomethyl)-1,3-propanediol (BBMP)		250 ppm		
13674-87-8	Tris(1,3-dichloro-isopropyl) phosphate (TDCP)		250 ppm		
85535-84-8	Short-chain chlorinated Paraffins (SCCP) (C10-C13)		50 ppm		
Glycols					
111-96-6	Bis(2-methoxyethyl)-ether		50 ppm		
110-80-5	2-ethoxyethanol		50 ppm	In apparel and footwear, glycols have a	
111-15-9	2-ethoxyethyl acetate		50 ppm	wide range of uses including as solvents	I lite to a second second
110-71-4	Ethylene glycol dimethyl ether	No intentional use	50 ppm	for finishing/cleaning, printing agents,	High-performance liquid
109-86-4	2-methoxyethanol	No intentional use	50 ppm	and dissolving and diluting fats, oils and	chromatography (HPLC), LC- MS
110-49-6	2-methoxyethylacetate		50 ppm	adhesives (e.g., in degreasing or	IVIS
70657-70-4	2-methoxypropylacetate		50 ppm	cleaning operations).	
112-49-2	Triethylene glycol dimethyl ether		50 ppm	1	
Halogenated Solven	ts				
107-06-2	1,2-dichloroethane		5 ppm	In apparel and footwear, solvents are	
75-09-2	Methylene chloride		5 ppm	used as finishing/cleaning and printing	
79-01-6	Trichloroethylene	No intentional use	40 ppm	agents, for dissolving and diluting fats,	GC-MS
127-18-4	Tetrachloroethylene		5 ppm	oils and adhesives (e.g., in degreasing or cleaning operations).	



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Apparel and Footwear Textile Processing	General Techniques for Analysing Chemicals
Organotin Compoun	ds				
Multiple	Dibutyltin (DBT)		20 ppm	Organotins are a class of chemicals	
Multiple	Mono-, di- and tri-methyltin derivatives		5 ppm	combining tin and organics such as butyl	
Multiple	Mono-, di- and tri-butyltin derivatives	7	5 ppm	and phenyl groups. Organotins are	
Multiple	Mono-, di- and tri-phenyltin derivatives		5 ppm	predominantly found in the environment	
Multiple	Mono-, di- and tri-octyltin derivatives	No intentional use	5 ppm	as antifoulants in marine paints, but they can also be used as biocides (e.g., antibacterials), catalysts in plastic and glue production and heat stabilisers in plastics/rubber. In textiles and apparel, organotins are associated with plastics/rubber, inks, paints, metallic glitter, polyurethane products and heat transfer material.	GC-MS, low resolution mass spectrometry (LRMS)
Polycyclic Aromatic	Hydrocarbons (PAHs)				
50-32-8	Benzo[a]pyrene (BaP)		20 ppm		
120-12-7	Anthracene		Polycyclic	Polycyclic aromatic hydrocarbons (PAHs)	1
129-00-0	Pyrene	1		are natural components of crude oil and	
191-24-2	Benzo[ghi]perylene			are a common residue from oil refining.	
192-97-2	Benzo[e]pyrene			PAHs have a characteristic smell similar	
193-39-5	Indeno[1,2,3-cd]pyrene	7		to the smell of car tires or asphalt. Oil	
205-82-3	Benzo[j]fluoranthene	7		residues containing PAHs are added to	
205-99-2	Benzo[b]fluoranthene	7		rubber and plastics as a softener or	
206-44-0	Fluoranthene			extender and may be found in rubber,	
207-08-9	Benzo[k]fluoranthene	7		plastics, lacquers and coatings. PAHs are	
208-96-8	Acenaphthylene	7		often found in the outsoles of footwear	
218-01-9	Chrysene	No intentional use	S 300	and in printing pastes of screen prints.	GC-MS
53-70-3	Dibenz[a,h]anthracene		Sum = 200 ppm	PAHs can be present as impurities in	
56-55-3	Benzo[a]anthracene			Carbon Black. They also may be formed	
83-32-9	Acenaphthene			from thermal decomposition of recycled materials during reprocessing.	
85-01-8	Phenanthrene			materials during reprocessing.	
86-73-7	Fluorene			Naphthalene: Dispersing agents for	
91-20-3				textile dyes may contain high residual naphthalene concentrations due to the use of low quality naphthalene derivatives (e.g., poor quality naphthalene sulphonate formaldehyde condensation products).	



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Apparel and Footwear Textile Processing	General Techniques for Analysing Chemicals				
Perfluorinated and Polyfluorinated Chemicals (PFCs)									
	Durable water, oil and stain repellent finishes and soil release finishes (fluorinated polymers) based on long-chain technology are banned from intentional use. Long-chain								
	g to the Organisation for Economic Co-operation a			<u>(pfc/)</u> are based on long-chain					
perfluorocarboxylic a	acids (C8 and higher) and on long-chain perfluoroall	kyl sulfonates (C6 and h	igher).						
Perfluoroalkyl sulfon	nts of this technology include: ates (PFSAs) with carbon chain lengths C6 and high acids with carbon chain lengths C8 and higher (e.g.,								
Naulat-I-	Perfluorooctane sulfonate (PFOS) and related		S 2	PFOA and PFOS may be present as					
Multiple	substances		Sum = 2 ppm	unintended by-products in long-chain					
Multiple	Perfluorooctanoic acid (PFOA) and related substances	No intentional use	Sum = 2 ppm	commercial water, oil and stain repellent agents. PFOA also may be in use for polymers like polytetrafluoroethylene (PTFE).	LC-MS				
Phthalates – includir	ng all other esters of ortho-phthalic acid								
117-81-7	Di(ethylhexyl) phthalate (DEHP)								
117-82-8	Bis(2-methoxyethyl) phthalate (DMEP)			Esters of ortho-phthalic acid (phthalates) are a class of organic compounds commonly added to plastics to increase flexibility. They sometimes					
117-84-0	Di-n-octyl phthalate (DNOP)								
26761-40-0	Di-iso-decyl phthalate (DIDP)								
28553-12-0	Di-isononyl phthalate (DINP)								
84-75-3	Di-n-hexyl phthalate (DnHP)			are used to facilitate moulding of plastic					
84-74-2	Dibutyl phthalate (DBP)			by decreasing its melting temperature.					
85-68-7	Butyl benzyl phthalate (BBP)			by decreasing its metting temperature.					
84-76-4	Dinonyl phthalate (DNP)	No intentional use	Sum of all phthalates	Phthalates can be found in:	GC-MS				
84-66-2	Diethyl phthalate (DEP)	No intentional use	= 250 ppm	Flexible plastic components	GC-IVIS				
131-16-8	Di-n-propyl phthalate (DPRP)			(e.g., PVC)					
84-69-5	Di-isobutyl phthalate (DIBP)			Print pastes					
84-61-7	Di-cyclohexyl phthalate (DCHP)			Adhesives					
27554-26-3	Di-iso-octyl phthalate (DIOP)			Plastic buttons					
68515-42-4	1,2-benzenedicarboxylic acid, di-C7-11-branched and linearalkyl esters (DHNUP)			Plastic sleevings Polymeric coatings					
71888-89-6	1,2-benzenedicarboxylic acid,di-C6-8-branched alkyl esters,C7-rich (DIHP)			r oryment cootings					



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Apparel and Footwear Textile Processing	General Techniques for Analysing Chemicals			
Total Heavy Metals								
	Listed metals are banned from intentional use in textile manufacturing/finishing. Additionally, residual traces of antimony, zinc, copper, nickel, tin, barium, cobalt, iron,							
	n and silver in colourants are expected to comply w	vith the Ecological and T	oxicological Association of Dyes and O	ganic Pigments Manufacturers (ETAD)				
concentration limits	http://www.etad.com/).							
7440-38-2	Arsenic (As)		50 ppm	Arsenic and its compounds can be used in some preservatives, pesticides and defoliants for cotton. It is also associated with synthetic fibres, paints, inks, trims and plastics.				
7440-43-9	Cadmium (Cd)		20 ppm (50 ppm for pigments)	Cadmium compounds are found in or used as: pigments (particularly red, orange, yellow and green), a stabiliser for PVC plastic and in fertilisers, biocides and paints (e.g., surface paints on zippers and buttons).	Inductively coupled plasma- optical emission			
7439-97-6	Mercury (Hg)	No intentional use	No intentional use	No intentional use	4 ppm (25 ppm for pigments)	Mercury compounds can be present in pesticides and can be found as contamination in caustic soda (NaOH). Mercury compounds may be used in paints (e.g., surface paints on zippers and buttons).	spectrometry (ICP-OES), atomic absorption spectroscopy (AAS)	
7439-92-1	Lead (Pb)		100 ppm	In apparel and footwear, lead may be associated with plastics, paints, inks, pigments and surface coatings.				
18540-29-9	Chromium (VI)		10 ppm	Although typically associated with leather tanning, chromium VI also may be used in the dyeing of wool (after the chroming process).				
Volatile Organic Com	pounds (VOC)							
71-43-2	Benzene		50 ppm	These volatile organic compounds)			
1330-20-7	Xylene		500 ppm	should not be used in textile auxiliary				
95-48-7	o-cresol		500 ppm	chemical preparations. They are				
106-44-5	p-cresol	No intentional usa	500 ppm	associated with solvent-based	GC MS			
108-39-4	m-cresol	No intentional use	500 ppm	processes like solvent- based polyurethane coatings and glues/adhesives. They should not be used for any kind of facility cleaning or spot cleaning.	GC-MS			



Chapter 2: MRSL for Leather Processing

CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Leather Processing for Apparel and Footwear	General Techniques for Analysing Chemicals within commercial formulations		
Alkylphenol (AP) and	d Alkylphenol Ethoxylates (APEOs): including a	ll isomers					
104-40-5 11066-49-2 25154-52-3 84852-15-3	Nonylphenol (NP), mixed isomers		250 ppm	APEOs can be used in leather processing or found in a variety of formulations such as	Liquid chromatography-mass spectrometry (LC-MS), gas chromatography-mass		
140-66-9 1806-26-4 27193-28-8	Octylphenol (OP), mixed isomers		250 ppm	detergents, wetting agents, emulsifier/ dispersing agents/dedusting agents for dyes and prints, dyes and pigment preparations, degreasing and fur scouring agents, fat liquors			
9002-93-1 9036-19-5 68987-90-6	Octylphenol ethoxylates (OPEO)	No intentional use	No intentional use	No intentional use	500 ppm	and greases, water borne dispersions and emulsions used in the beamhouse and finishing agents.	spectrometry (GC-MS) EN ISO 18219 -1 EN ISO 18219 - 2
9016-45-9 26027-38-3 37205-87-1 68412-54-4 127087-87-0	Nonylphenol ethoxylates (NPEO)		500 ppm	NP and OP are not used by the leather industry, but could be present as contaminants.	EN 130 10213 - 2		
Chlorobenzenes and	Chlorotoluenes						
95-50-1	1,2-dichlorobenzene		1000 ppm	Chlorobenzenes and chlorotoluenes can be			
	no-, di-, tri-, tetra-, penta- and hexa- nono-, di-, tri-, tetra- and penta-	No intentional use	Sum = 200 ppm	used for degreasing sheep and pig skins. They can also be used as solvents (e.g., in chemical synthesis).	GC-MS		



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Leather Processing for Apparel and Footwear	General Techniques for Analysing Chemicals within commercial formulations
Chlorophenols					
25167-83-3	Tetrachlorophenol (TeCP)		Sum = 20 nnm		
87-86-5	Pentachlorophenol (PCP)		Sum = 20 ppm		
4901-51-3	2,3,4,5-tetrachlorophenol]]	
58-90-2	2,3,4,6-tetrachlorophenol	1			
935-95-5	2,3,5,6-tetrachlorophenol	1			
95-57-8	2-chlorophenol	1	Chlorophenols are polychlorinated		
120-83-2	2,4-dichlorophenol	1		Chlorophenols are polychlorinated compounds used as preservatives or pesticides. Pentachlorophenol (PCP) and tetrachlorophenol (TeCP) have been used in the past to prevent mould when storing/transporting, raw hides	
583-78-8	2,5-dichlorophenol	1			
87-65-0	2,6-dichlorophenol	1			GC-MS
95-95-4	2,4,5-trichlorophenol	No intentional use			EN ISO 17070
88-06-2	2,4,6-trichlorophenol	1	Sum = 50 ppm		EN 150 17070
591-35-5	3,5-dichlorophenol	1		and leather. They are now regulated and should	
576-24-9	2,3-Dichlorophenol	1		not be used.	
95-77-2	3,4-Dichlorophenol	1			
108-43-0	3-Chlorophenol	1			
106-48-9	4-Chlorophenol				
15950-66-0	2,3,4-Trichlorophenol				
933-78-8	2,3,5-Trichlorophenol	1			
609-19-8	3,4,5-Trichlorophenol	1			



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Leather Processing for Apparel and Footwear	General Techniques for Analysing Chemicals within commercial formulations
Dyes – Azo (Forming	Restricted Amines)				
101-14-4	4,4'-methylene-bis-(2-chloro-aniline)		150 ppm		
101-77-9	4,4'-methylenedianiline]	150 ppm		
101-80-4	4,4'-oxydianiline] [150 ppm		
106-47-8	4-chloroaniline		150 ppm		
119-90-4	3,3'-dimethoxylbenzidine		150 ppm		
119-93-7	3,3'-dimethylbenzidine]	150 ppm]	
120-71-8	6-methoxy-m-toluidine]	150 ppm	Azo dyes and pigments are colourants that	
137-17-7	2,4,5-trimethylaniline	1 1	150 ppm	incorporate one or several azo groups	
139-65-1	4,4'-thiodianiline]	150 ppm	(-N=N-) bound with aromatic compounds. Thousands of azo dyes exist, but only those which degrade to form the listed cleavable amines are restricted. Azo dyes that release these amines are regulated and should no longer be used for dyeing of leather.	
60-09-3	4-aminoazobenzene]	150 ppm		10.001
615-05-4	4-methoxy-m-phenylenediamine] [150 ppm		LC, GC-MS
838-88-0	4,4'-methylenedi-o-toluidine	No intentional use	150 ppm		EN ISO 17234 - 1
87-62-7	2,6-xylidine	No intentional use	150 ppm		EN ISO 17234 – 1 EN ISO 17234 – 2
90-04-0	o-anisidine	1 1	150 ppm		EN 130 17234 - 2
91-59-8	2-naphthylamine] [150 ppm	Restricted amines also may be present or	
91-94-1	3,'3-dichlorobenzidine]	150 ppm	formed during cleavage of unintended	
92-67-1	4-aminodiphenyl	1 1	150 ppm	impurities in raw materials used for dyestuff	
92-87-5	Benzidine]	150 ppm	production.	
95-53-4	o-toluidine] [150 ppm		
95-68-1	2,4-xylidine]	150 ppm]	
95-69-2	4-chloro-o-toluidine	1 1	150 ppm]	
95-80-7	4-methyl-m-phenylenediamine]	150 ppm]	
97-56-3	o-aminoazotoluene]	150 ppm		
99-55-8	5-nitro-o-toluidine		150 ppm]	
Dyes – Navy Blue Co	blourant				
118685-33-9	Component 1: C39H23ClCrN7O12S-2Na			Navy Blue colourants are regulated, were not	LC
Not Allocated	Component 2: C46H30CrN10O20S2-3Na	No intentional use	250 ppm	sold commercially, and should not have been used for dyeing of leather	(No test reference available)



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Leather Processing for Apparel and Footwear	General Techniques for Analysing Chemicals within commercial formulations
Dyes – Carcinogenio	or Equivalent Concern				
1937-37-7	C.I. Direct Black 38		250 ppm		
2602-46-2	C.I. Direct Blue 6		250 ppm		
3761-53-3	C.I. Acid Red 26		250 ppm		
569-61-9	C.I. Basic Red 9		250 ppm		
573-58-0	C.I. Direct Red 28		250 ppm		
632-99-5	C.I. Basic Violet 14		250 ppm		
2475-45-8	C.I. Disperse Blue 1		250 ppm	Most of these substances are regulated in many countries. All should no longer be used for dyeing of leather.	LC
2475-46-9	C.I. Disperse Blue 3	No intentional use	250 ppm		
2580-56-5	C.I. Basic Blue 26 (with Michler's Ketone > 0.1%)		250 ppm		
569-64-2	C.I. Basic Green 4 (malachite green chloride)		250 ppm		
2437-29-8	C.I. Basic Green 4 (malachite green oxalate)		250 ppm		
10309-95-2	C.I. Basic Green 4 (malachite green)		250 ppm		
82-28-0	Disperse Orange 11		250 ppm		
Dyes – Disperse (Se	nsitizing)				
		Disperse dyes have	no applicability to leather pro	ocessing.	
Fat liquoring agents					
85535-84-8	Short-chain chlorinated paraffin ($C_{10}-C_{13}$)	No intentional use	250 ppm	Short-chain chlorinated paraffins can be found as contaminants within long-chain chlorinated paraffins and sulfo-chlorinated paraffin's, used as fat liquoring agents.	Gas chromatography/ electron capture negative ion-mass spectrometry (GC/ECNI-MS) EN ISO 18219



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Leather Processing for Apparel and Footwear	General Techniques for Analysing Chemicals within commercial formulations
Flame Retardants					
115-96-8	Tris(2-chloroethyl)phosphate (TCEP)	-	250 ppm	Flame retardant chemicals are rarely used to meet flammability requirements in children's clothing and adult products, but they could be used in processing leather for technical/industrial purposes (e.g., drive belts) and upholstery leather for trains and planes. The mentioned substances should no longer be used in apparel and footwear.	GC-MS
1163-19-5	Decabromodiphenyl ether (DecaBDE)		250 ppm		
126-72-7	Tris(2,3,-dibromopropyl)-phosphate (TRIS)		250 ppm		
32534-81-9	Pentabromodiphenyl ether (PentaBDE)		250 ppm		
32536-52-0	Octabromodiphenyl ether (OctaBDE)		250 ppm		
5412-25-9	Bis(2,3-dibromopropyl)phosphate (BIS)		250 ppm		
545-55-1	Tris(1-aziridinyl)phosphine oxide) (TEPA)]	250 ppm		
59536-65-1	Polybromobiphenyls (PBB)	No intentional use	250 ppm		
79-94-7	Tetrabromobisphenol A (TBBPA)]	250 ppm		
3194-55-6	Hexabromocyclodecane (HBCDD)		250 ppm		
3296-90-0	2,2-bis(bromomethyl)-1,3-propanediol (BBMP)		250 ppm		
13674-87-8	Tris(1,3-dichloro-isopropyl) phosphate (TDCP)		250 ppm		
Glycol Ethers				•	•
111-96-6	Bis(2-methoxyethyl)-ether		50 ppm	In apparel and footwear, glycol ethers have a	
110-80-5	2-ethoxyethanol]	50 ppm	wide range of uses including as solvents for	
111-15-9	2-ethoxyethyl acetate		50 ppm	finishing/cleaning, printing agents and	
110-71-4	Ethylene glycol dimethyl ether		50 ppm	dissolving and diluting fats, oils and adhesives	
109-86-4	2-methoxyethanol		50 ppm	(e.g., in degreasing or cleaning operations).	111-h f 11 1
110-49-6	2-methoxyethylacetate	No intentional use	50 ppm	Some polar solvents (glycol ethers) are	High-performance liquid
112-49-2	Triethylene glycol dimethyl ether	No intentional use -	50 ppm	necessary for the use of water-based leather finishing systems. The mentioned glycol ethers are classified as carcinogenic, mutagenic or reprotoxic substances and should not be used in processing leather.	chromatography (HPLC), LC- MS
70657-70-4	2-methoxypropylacetate		1000 ppm		1
Halogenated Solver				'	'
107-06-2	1,2-dichloroethane		5 ppm	In apparel and footwear, solvents are used as	
75-09-2	Methylene chloride	No laborational con-	5 ppm	finishing/cleaning and printing agents, for	66.146
79-01-6	Trichloroethylene	No intentional use	40 ppm	dissolving and diluting fats, oils and adhesives	GC-MS
127-18-4	Tetrachloroethylene		5 ppm	(e.g., in degreasing or cleaning operations).	
	<u> </u>	-	• • • • • • • • • • • • • • • • • • • •		+



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Leather Processing for Apparel and Footwear	General Techniques for Analysing Chemicals within commercial formulations
Organotin Compoun	ds				
Multiple	Dibutyltin (DBT)	No intentional use	20 ppm (*EXCEPTION* 100 ppm for polyurethane based thickeners used at <20% loading)	Organotins are a class of chemicals combining tin and organics such as butyl and phenyl groups. Organotins are predominantly found in the environment as antifoulants in marine paints, but they can also be used as biocides (e.g., antibacterials), catalysts in plastic and glue productions and heat stabilizers in	GC-MS, low resolution mass spectrometry (LRMS)
Multiple	Mono-, di- and tri-methyltin derivatives	The interitional asc	5 ppm		
Multiple	Mono-, di- and tri-butyltin derivatives		5 ppm	plastics/rubber.	
Multiple	Mono-, di- and tri-phenyltin derivatives		5 ppm	Polyurethane thickeners, which could contain traces of DBT, are commonly used for viscosity adjustments of leather chemicals formulations.	
Multiple	Mono-, di- and tri-octyltin derivatives]	5 ppm		
Polycyclic Aromatic	Hydrocarbons (PAHs)				
50-32-8	Benzo[a]pyrene (BaP)		20 ppm		
120-12-7	Anthracene]			
129-00-0	Pyrene]			
191-24-2	Benzo[ghi]perylene				
192-97-2	Benzo[e]pyrene				
193-39-5	Indeno[1,2,3-cd]pyrene				
205-82-3	Benzo[j]fluoranthene		Polycyclic aromatic hydrocarbons (PAHs) are natural components of crude oil and are a	, , , , , , , , , , , , , , , , , , , ,	
205-99-2	Benzo[b]fluoranthene				
206-44-0	Fluoranthene		Sum = 300 anm	common residue from oil refining. PAHs are typically found as contaminants within leather formulations.	GC-MS
207-08-9	Benzo[k]fluoranthene		Sum = 200 ppm		
208-96-8	Acenaphthylene	No intentional use			
218-01-9	Chrysene	No intentional use			
53-70-3	Dibenz[a,h]anthracene				
56-55-3	Benzo[a]anthracene				
83-32-9	Acenaphthene				
85-01-8	Phenanthrene				
86-73-7	Fluorene				
91-20-3	Naphthalene		300 ppm	In the leather chemical industry, naphthalene is used as a raw material for manufacture of synthetic tanning agents (syntans) and for manufacture of active substances in dispersing agents used during leather processing.	GC-MS, LC



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Leather Processing for Apparel and Footwear	General Techniques for Analysing Chemicals within commercial formulations		
Perfluorinated and Polyfluorinated Chemicals (PFCs)							
Durable water, oil an	nd stain repellent finishes and soil release finish	es (fluorinated polymers) b	ased on long-chain technolo	gy are banned from intentional use. Long-chain			
	ng to the Organisation for Economic Co-operatio acids (C8 and higher) and on long-chain perfluor			cd.org/ehs/pfc/) are based on long-chain			
Perfluoroalkyl sulfon	The main contaminants of this technology include: Perfluoroalkyl sulfonates (PFSAs) with carbon chain lengths C6 and higher (e.g., PFOS, perfluorooctane sulfonate) Perfluorocarboxylic acids with carbon chain lengths C8 and higher (e.g., PFOA, perfluorooctanoic acid)						
Multiple	Perfluorooctane sulfonate (PFOS) and related substances	No intentional use	Sum = 2 ppm	PFOA and PFOS may be present as unintended by-products in long-chain commercial water, oil	16.16		
Multiple	Perfluorooctanoic acid (PFOA) and related substances		Sum = 2 ppm	and stain repellent agents. PFOA also may be in use for polymers like polytetrafluoroethylene (PTFE).	LC-MS		
Phthalates – includir	ng all other esters of ortho-phthalic acid						
117-81-7	Di(ethylhexyl) phthalate (DEHP)						
117-82-8	Bis(2-methoxyethyl) phthalate (DMEP)						
117-84-0	Di-n-octyl phthalate (DNOP)		Esters of ortho-phthalic acid (phthalates) are				
26761-40-0	Di-iso-decyl phthalate (DIDP)			Esters of ortho-phthalic acid (phthalates) are a			
28553-12-0	Di-isononyl phthalate (DINP)						
84-75-3	Di-n-hexyl phthalate (DnHP)			class of organic compounds commonly added to			
84-74-2	Dibutyl phthalate (DBP)		plastics t	plastics to increase flexibility. They are sometimes used to facilitate moulding of plastic			
85-68-7	Butyl benzyl phthalate (BBP)						
84-76-4	Dinonyl phthalate (DNP)	No intentional use	Sum of all phthalates by decreasing its melting temperature.	GC-MS			
84-66-2	Diethyl phthalate (DEP)	No intentional use	= 250 ppm		GC-IVI3		
131-16-8	Di-n-propyl phthalate (DPRP)			Polymeric coatings for leather finishing,			
84-69-5	Di-isobutyl phthalate (DIBP)			dedusting agents in colourants, fat liquors and			
84-61-7	Di-cyclohexyl phthalate (DCHP)			greases could be a source for phthalates in			
27554-26-3	Di-iso-octyl phthalate (DIOP)			formulations for leather processing.			
68515-42-4	1,2-benzenedicarboxylic acid, di-C7-11- branched and linearalkyl esters (DHNUP)						
71888-89-6	1,2-benzenedicarboxylic acid,di-C6-8- branched alkyl esters,C7-rich (DIHP)						



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Leather Processing for Apparel and Footwear	General Techniques for Analysing Chemicals within commercial formulations
Total Heavy Metals					
Listed metals are bar manganese, seleniun concentration limits					
7440-38-2	Arsenic (As)	No intentional use	50 ppm	Arsenic and its compounds can be used in some preservatives, pesticides and defoliants for cotton. It is also associated with synthetic fibres, paints, inks, trims and plastics. Arsenic is not a typical residue in leather chemicals.	
7440-43-9	Cadmium (Cd)		20 ppm (50 ppm for pigments)	Cadmium compounds are found in or used as: pigments (particularly red, orange, yellow and green), a stabiliser for PVC plastic and in fertilisers, biocides and paints (e.g., surface paints on zippers and buttons).	Inductively coupled plasma- optical emission spectrometry (ICP-OES), atomic absorption
7439-97-6	Mercury (Hg)		4 ppm (25 ppm for pigments)	Mercury compounds can be present in pesticides and can be found as contamination in caustic soda (NaOH). Mercury compounds may be used in paints (e.g., surface paints on zippers and buttons). Mercury is not a typical residue in leather	spectroscopy (AAS) Cr (III) Tanning agents can be
7439-92-1	Lead (Pb)		100 ppm	chemicals. In apparel and footwear, lead may be associated with plastics, paints, inks, pigments and surface coatings.	monitored for Cr(VI) EN ISO 17075 (Current Use) ISO/DIS 19071 (Draft)
18540-29-9	Chromium (VI)		10 ppm	The two-bath process for tanning using potassium dichromate (VI) is no longer used by the leather industry. Potassium dichromate (VI) and other chromium (VI) compounds are banned and chromium (VI) residues in chromium (III) tanning agents are restricted.	



CAS No.	Substance	Group A: Raw Material and Finished Product Supplier Guidance	Group B: Chemical Supplier Commercial Formulation Limit	Potential Uses in Leather Processing for Apparel and Footwear	General Techniques for Analysing Chemicals within commercial formulations		
Volatile Organic Con	Volatile Organic Compounds (VOC)						
71-43-2	Benzene	No intentional use	50 ppm	These volatile organic compounds should not			
95-48-7	o-cresol		500 ppm	be used in textile and leather auxiliary chemical			
106-44-5	p-cresol		500 ppm	preparations. They are associated with solvent-			
				based processes like solvent-based	GC-MS		
100.20.4	1		500	polyurethane coatings and glues/adhesives.			
108-39-4	m-cresol		500 ppm	They should not be used for any kind of facility			
				cleaning or spot cleaning.			